

explorer

PHOTO & VIDEO


Explorer TX-VK Carbon Travel Tripod



Specifications

MODEL	MATERIAL	MINIMUM HEIGHT	MAXIMUM HEIGHT	MAX LOAD	WEIGHT	FOLDED LENGTH	SECTIONS	MAX LEG DIAMETER
TX-VK	10X Carbon	16.5cm/ 6.49"	153cm/ 60.23"	14kgs/ 30.86lbs	1.23kgs/ 2.71lbs	35cm/ 13.78"	5	2.45cm/ 0.95"

Components



- ① Ball head with 3/8" Mounting Screw
- ② Reversible centre column
- ③ Leg angle adjustment (3 angles available)
- ④ Leg lock
- ⑤ Monopod
- ⑥ Stabilising hook
- ⑦ Multifunctional mount (Used for mounting other gear for e.g. microphone or light etc)

Maintenance

1. Prevent the tripod ball head from getting fouled in mud, dirt or sand
2. Blow off any sand or dust, or wipe it off with a soft cloth
3. Rinse any mud, dirt salt water and dry it thoroughly
4. Do not submerge the ball head in liquid
5. Do not apply any lubricant
6. Do not remove any of the knobs. this can damage the threads and ball locking mechanism.
7. If used around salt water wash with fresh cold water and let dry before collapsing the tripod.

Operating Instructions

Leg angle adjustment

To change the angle of the tripod leg, pull out the tab and pull the leg to the desired angle (3 options). Push the tab back in place to lock it to the desired angle.



Leg locks

To adjust the height of the tripod, twist the leg locks a 1/2 twist clock wise to release the leg. Pull out to the desired height and 1/2 twist counter clock wise to secure into place. Ensure these are tightly secured before removing hand off tripod.



Accessory ports

3/8" and 1/4" accessory ports are located on the centre junction to mount accessories. To mount simply screw the accessory into the relevant port.



Convert leg to monopod

The leg with a grip converts into a monopod. Twist anti-clockwise to unscrew the leg. Unscrew the hook and remove the centre column, base plate and head. Screw this into the monopod leg. There is an additional base plate included so that the monopod can be used without the centre column as well.



Reversible/removable centre column

The centre column is reversible to allow the user to get their camera closer to the ground. To reverse simply unscrew the hook at the base of the centre column and unscrew the column from the grip closest to the base. Once unscrewed either remove the column or reverse it and reattach the screw.

No centre column



Unscrew hook

Centre column reversed



1. Working temperature -40C- 60C
2. Ensure all leg locks are secure before taking your hand off the tripod
3. Do not use the tripod for anything other than its intended use
4. Do not exceed max load limit

EXPLORE | CAPTURE | CREATE

Follow us on Instagram

@explorerphotovideo



Explorer Photo and Video

Sydney, Australia

Los Angeles, United States of America

W: explorerphotovideo.com

E: hello@explorerphotovideo.com